Calhoun
Institutional Archive of the Naval Postgraduate School

Calhoun: The NPS Institutional Archive

DSpace Repository

Theses and Dissertations | 1. Thesis and Dissertation Collection, all items

1949-08

The analytical design of a turbo-jet combustion chamber.

Verdin, James Bernard

University of Minnesota

Downloaded from NPS Archive: Calhoun

DUDLEY KNOX LIBRARY

http://www.nps.edu/library

Calhoun is the Naval Postgraduate School's public access digital repository for research materials and institutional publications created by the NPS community. Calhoun is named for Professor of Mathematics Guy K. Calhoun, NPS's first appointed -- and published -- scholarly author.

Dudley Knox Library / Naval Postgraduate School
411 Dyer Road / 1 University Circle
Monterey, California USA 93943

Thesis
V4

Library
U. S. Naval Postgraduate School
Annapolis, Md.

THE ANALYTICAL DESIGN OF A TURBO-JET COMBUSTION CHAMBER

A Thesis Submitted to the Graduate Faculty

of the

University of Minnesota

by

James B. Verdin

In Partial Fulfillment of the Requirements

for the

Degree of

Master of Science in Aeronautical Engineering

August 1949

F1

ACKNOWLEDGMENTS

I wish to express my thanks to Professors S. J. Robertson, N. A. Hall, T. E. Murphy and J. D. Akerman for their advice and encouragement and to my wife, Muriel, for her help in preparing the manuscript.

11164

TABLE OF CONTENTS

Section		Page
I.	SUMMARY	1
II.	INTRODUCTION	2
III.	PURPOSE OF INVESTIGATION	4
IV.	PROBLEMS INVOLVED IN THE DESIGN OF A COMBUSTION CHAMBER	5
V.	SELECTION OF THE DESIGN POINT	9
VI.	DESIGN PROCEDURE AND CALCULATIONS	14
	Maximum Diameter of Combustion Chamber	14
	Fuel Required	15
	Primary Air Required	16
	Volume Available for Combustion	16
	Configuration of Burner Basket	17
	Design of Primary Zone	20
	Design of Secondary Zone	28
	Louvres	28
	Tail Cone Annulus	29
	Secondary Holes	32
	Check of Air Flow	34
	Location of Holes	34
VII.	CALCULATION OF PERFORMANCE	38
	Friction Pressure Drop	38
	Momentum Pressure Drop	38
	Total Pressure Drop	45
	Combustion Efficiency	46

Table of Contents

Section Page

I. [illegible] 1

II. [illegible] 3

III. Objects of Investigation 4

IV. [illegible] 5

V. Methods of the Study 8

VI. [illegible] 14

Natural Boundaries of Cultivated Plants 14

Plant Geography 15

Natural Regions of Cultivated Plants 19

Primary Centers of Origin 19

Secondary Centers of Origin 22

Dispersal of Primary Types 23

Dispersal of Secondary Types 29

Dispersal of Hybrids 33

Cell Lines 36

Secondary Centers 37

Change of Life Form 37

Dominance of Hybrids 38

VII. [illegible] 39

Reasons for Variation 39

Genetic Variation 40

Visual Variation 42

Somatic Variation 46

TABLE OF CONTENTS

(Continued)

Page

VIII. CONCLUSIONS..... 48

Appendix

A. OBSERVATION OF FLOW THROUGH SECONDARY HOLES OF A TURBO-JET COMBUSTION CHAMBER..... 50

Summary..... 50

Introduction..... 50

Equipment..... 51

Procedure..... 55

Results..... 57

Conclusions..... 58

Sample Calculations..... 64

B. SYMBOLS..... 65

C. REFERENCES..... 68

D. BIBLIOGRAPHY..... 69

LIST OF TABLES

Table Page

I. Design Factors for Combustion Chambers of Current Model Turbo-Jet Engines..... 10

II. Flow Angle through Holes for Various Weight Flows..... 59

List of Appendices

(Continued)

Appendix

A111. Questionnaire 76

LIST OF FIGURES

Figure		Page
1.	Effect of Hole Mouth Shape on Mixing.....	8
2.	Effect of Hole Shape on Mixing.....	8
3.	Combustion Loss Vs. Combustion Intensity for Lucas B-37 Chamber.....	12
4.	Sketch of Burner Basket, Dome, and Tail Cone.....	18
5.	Cutaway Diagram of Combustion Chamber Showing Flow of Air.....	21
6.	Curve Used in Locating Primary and Secondary Holes	35
7.	Designed Combustion Chamber.....	37
8.	Photograph of Test Setup for Observing Angle of Flow.....	52
9.	Another View of Test Setup for Observing Angle of Flow.....	53
10.	Close-up View of Smoke Generator.....	54
11.	Close-up View of Test Box.....	56
12.	Flow Angle through Holes for Various Weight Flows	60
13.	Interior of Test Box Showing Angle of Silk Tufts During Run at 1.18 Lb/Sec.....	61
14.	Interior of Test Box Showing Angle of Silk Tufts During Run at 1.45 Lb/Sec.....	62
15.	Interior of Test Box During Run in Which Smoke Generator Was Used.....	63

LIST OF FIGURES

Figure Page

1. Effect of Pile Group Spacing on Stiffness..... 6

2. Effect of Pile Group on Stiffness..... 8

3. Comparison Loads for Penetration Increment for Vesic D-22 Standard..... 12

4. Layout of Tension Element, Load Cell Compression Dynamometer..... 14

5. Load at Different Penetration Increments..... 21

6. Values Used in Computing Ultimate and Theoretical Loads..... 23

7. Analytical Correlation Chart..... 24

8. Relationship of Load Ratio for Theoretical Value of Load..... 26

9. Correlation Plots for Interacting Piles of Group..... 28

10. Correlation Plots of Load Ratio..... 34

11. Correlation Plots of Load Ratio..... 39

12. Correlation Plots of Load Ratio..... 44

13. Plots Showing Efficiency Ratio for Various Spacing Plans 49

14. Interaction of Load for Bearing Piles of Plan Spacing Ratio of 2.11 Diameter..... 53

15. Interaction of Load for Bearing Piles of Plan Spacing Ratio of 3.00 Diameter..... 55

16. Interaction of Load for Bearing Piles of Plan Spacing Ratio of 4.00 Diameter..... 57

I. SUMMARY

A "can" type combustion chamber was designed using all available proved concepts. A survey of existing designs was made to arrive at a logical design point. The fact that parallel flow would exist within the chamber was noted, and the burner was designed to obtain the required flow with an equal pressure drop across all the parallel paths. The holes for introducing the air into the burner basket were placed in such a manner that the total area into the burner basket, plotted against distance downstream, fell on an arc of a circle. This made the design follow several proved concepts automatically.

The performance was calculated and compared with existing designs. The comparison was quite favorable, with the exception of combustion efficiency. Since the empirical equation for combustion efficiency was obtained from tests under slightly different conditions than the design point, doubt exists as to the validity of the values obtained by its use.

II. INTRODUCTION

Many combustion chambers for turbo-jet engines have been built and tested; however, they all fall into one of two classifications. The most common type is the tube or "can" combustion chamber. The other is the annular type.

The "can" type of combustion chamber, as its name implies, is a metal cylinder or can with an inner liner or "basket" which separates the air into two parts. The early turbo-jet engines designed by Air Commodore F. Whittle of Great Britain used "can" combustion chambers of the "return flow" type. In this type of chamber, the air passes over the entire length of the combustion zone before entering to be mixed with the fuel and burned. Thus the air is pre-heated by what would otherwise be waste heat. This advantage is more than overcome by the disadvantage of a high pressure loss. The more modern "can" type combustion chambers are of the "straight through" variety, i.e., there are no turns encountered within the chamber itself.

The annular type of combustion chamber has the distinct advantage of offering less frontal area for a given capacity than a battery of "cans" of equal capacity. The annular combustion chamber has the disadvantage of having to be tested in its entirety, while one "can" of a multi-can battery can be tested. Work is being done at Westinghouse in testing a small segment of an annular chamber and using the results to predict the performance of the complete unit.

IV. Conclusion

Many commentators cite Marbe-Ibi warning some

No results have been published, but it is expected that this method of testing will prove satisfactory.

Since the "can" type combustion chamber is more easily built and the testing procedures for the chamber are more nearly standardized, it was decided to base the analytical design on this type of combustion chamber.

III. PURPOSE OF INVESTIGATION

"Cut and try" has been the method employed in the past in designing combustion chambers for turbo-jet engines. This is a long and costly process, and luck plays a considerable part in obtaining results. It is the purpose of this investigation to design a combustion chamber using analytical methods. Proved concepts will be used where they are available. It is hoped that this procedure will produce a satisfactory chamber with little or no alteration necessary.

IV. PROBLEMS INVOLVED IN THE DESIGN OF A COMBUSTION CHAMBER

The function of a turbo-jet combustion chamber is to heat the air from the compressor to the temperature required at the entrance to the turbine. This temperature is usually taken to be 1500° F, this being the maximum temperature at which present day turbine wheels can operate. Sufficient fuel to achieve this temperature gives a fuel-air ratio far too lean for satisfactory combustion. Therefore, the air is divided into primary air and secondary air, the primary air being just sufficient to produce a stoichiometric fuel-air mixture with the required fuel and the secondary air being introduced to cool the products of combustion before reaching the turbine.

The primary air must be introduced into the combustion chamber with enough turbulence to insure good mixing with the fuel. This turbulence also speeds the burning and gives a stable flame.

The secondary air must be brought in with enough large-scale turbulence to complete the burning and to mix thoroughly with the products of combustion. Any stratification due to incomplete mixing will result in layers of air at temperatures higher than the allowable reaching the turbine. Hot spots will be caused, and a failure of the metal may occur.

High turbulence and a long combustion chamber tend to give more complete burning and better mixing of secondary

air and combustion products. Unfortunately, these characteristics are not compatible with an efficient design. High turbulence produces high pressure losses through the combustion chamber. Since compressor efficiencies and pressure ratios are critical, the additional pressure loss which results from high turbulence must be avoided. Therefore, just enough turbulence to complete the mixing should be used. Anything in excess of this, while insurance against turbine hot spots, cuts down the combustion chamber efficiency.

Since turbo-jet engines are used on airplanes, space and weight are at a premium. This precludes the use of an excessively long combustion chamber to complete the mixing. Lengths of three to four diameters are current practice.

The rate at which the secondary air is mixed with the combustion products is of great importance. Too much air introduced too soon may chill the flame front sufficiently to prevent the combustion reaction from going to completion. This, of course, would reduce the combustion efficiency. Reference 1 states that the first secondary air should not be introduced nearer than six to eight inches downstream from the fuel nozzle.

Experiments conducted at the California Institute of Technology show that the shape of the holes used to let the air through the inner liner has an effect on the pressure drop through these holes and also an effect on the mixing of the air with the combustion products. Figures 1 and 2 show the effects of shape on mixing. A thin slot parallel to the

flow gives the best mixing, a square or circular hole next best, and a slot perpendicular to the flow the worst.

The square hole and the slot are undesirable, however, because high stress concentrations would be produced at the sharp corners.

The round hole has found almost universal acceptance. The use of a bell mouth on these holes reduces the pressure drop across the holes by nearly thirty per cent without affecting the mixing.

These experiments also showed that arranging the holes in lines with one hole directly downstream from the other gave the greatest amount of turbulence for a given pressure drop.

Since there are no facilities available for testing the altitude performance of a combustion chamber, no attempt will be made to take this requirement into consideration.



FIGURE 1
EFFECT OF HOLE MOUTH SHAPE ON MIXING.
(FROM REF. 1)



FIGURE 2
EFFECT OF HOLE SHAPE ON MIXING.
(FROM REF. 1)

V. SELECTION OF THE DESIGN POINT

In order to arrive at a suitable design point, a survey of several current model turbo-jet engines was made. Table I lists the design factors for the combustion chambers of these engines.

The "loading factor" or "combustion intensity factor," as it is sometimes called, is a parameter originated by the British for comparing different combustion chambers. It is defined as follows:

$$I = \frac{q}{PV}$$

where q = heat input in Btu/hr

P = pressure inside chamber in atmospheres

V = volume available for combustion inside basket in ft^3

I = loading factor in Btu/hr-ft^3-atm.

The heat input is computed by multiplying the fuel flow rate in pounds per hour by the lower heating value of the fuel. The volume available for combustion inside the basket is taken from the fuel injection nozzle to the turbine entrance.

It can readily be seen that the combustion intensity factor is a good indication of the conditions under which combustion takes place. For instance, for a given heat input, the larger the volume available for combustion, the greater will be the amount of air available to absorb the heat released and, consequently, the lower is the intensity

8. Derivation of the Poisson Model

In order to derive a multiple regression model, a mathematical model of regression should first be established. Let us begin with the simplest case of linear regression, one dependent variable and one independent variable. Let the dependent variable be denoted by y and the independent variable by x. Then the regression equation is

$$y = \frac{kx}{1}$$

where k = some factor in y/x.

k = difference between the observations

1 = increase in the independent variable

The above model is assumed to satisfy the following conditions:

1 = Constant linear increase in y/x-ratio.

$\frac{kx}{1}$ = difference between the observations

k = ratio of the dependent variable to the independent variable

x = independent variable

y = dependent variable

1 = constant increase in y/x-ratio.

The above model is assumed to satisfy the following conditions:

1. Constant linear increase in y/x-ratio.
2. Difference between the observations
3. Ratio of the dependent variable to the independent variable
4. Independent variable
5. Dependent variable
6. Constant increase in y/x-ratio.

factor. Again, for a given heat input and a given volume available for combustion, the lower the pressure, the smaller will be the mass of air and the higher is the temperature rise from combustion; hence, the combustion intensity factor will be higher.

Table I. Design Factors for Combustion Chambers of Current Model Turbo-Jet Engines.*

Engine	N	v_r	I	D	l/D	L/D
TG-180 (J-35)	8	100	3.1×10^6	7.3	3.35	4.80
I-40 (J-38)	14	130	4.6×10^6	5.5	3.80	4.80
Nene	9	80	2.0×10^6	10.0	2.20	2.70
Derwent V	9	80	2.0×10^6	10.0	2.60	3.30
Goblin II	16	100	3.5×10^6	6.0	3.20	4.50
19XB	Annular	-	9.0×10^6	-	-	-
9.5B	Annular	-	10.0×10^6	-	-	-

* I - Loading factor or combustion intensity factor, Btu per hour per cubic foot per atmosphere, based on total volume available for combustion and mixing.

N - Number of combustion chambers.

l - Length in inches from fuel nozzle to end of basket.

L - Length in inches from fuel nozzle to turbine entrance.

v_r - Reference velocity in feet per second, computed using maximum cross-sectional area of combustion chamber.

D - Diameter of basket in inches.

The British have tried to correlate this combustion intensity factor with combustion losses. While no close

Lumber. Again, for a given load factor and a given moisture
available for combustion, the lower the pressure, the
smaller will be the mass of air and the higher is the temper-
ature rise (combustion) known, the combustion intensity
factor will be higher.

Table 1. Typical Factors for Incomplete Combustion of Various
Wood Furnace-Fuel Systems.

Species	f	m_p	i	e	E_{ff}	I_{cf}
Pine (Soft)	6	120	1.1×10^6	2.2	0.52	4.40
Oak (Hard)	14	180	4.8×10^6	8.8	1.46	4.40
Mean	9	60	2.0×10^6	30.0	0.20	6.40
Uniform I	0	40	2.0×10^6	30.0	0.60	4.20
Uniform II	14	120	2.0×10^6	0.0	0.80	4.40
Zero	Anomalous	-	0.0×10^6	-	-	-
N.D.	Anomalous	-	10.0×10^6	-	-	-

f = Loading factor or moisture intensity factor, lbs
dry fuel/ hr cubic ft. per atmosphere, based on
total volume available for combustion and stored.

m = Number of combustion chambers.

i = Density in inches from dust deposit to end of passage.

e = Length in inches from dust deposit to starting chamber.

E_{ff} = Efficiency ratio(by in feet per second) weighted ratio
maximum across-restricted area of combustion chamber.

I = Diameter of passage in inches.

I_{cf} = Incineration index factor for uncorrected ratio combustion

correlation exists between different combustion chambers, curves of individual chambers show that combustion losses increase rapidly with increasing combustion intensity factor. A typical graph of combustion losses vs. combustion intensity factor is presented in Figure 3 for the Lucas B-37 chamber. However, these losses may be inordinately high since, at sea level, values of combustion intensity factor as high as 9×10^6 are possible with a combustion efficiency of 95 per cent (Ref. 2).

The reference velocity, V_r, is another British parameter. It is used to get a rough check on the total losses through the combustion chamber. Reference 3 shows that individual combustion chambers have a pressure loss of from 20 to 30 times the velocity head computed for the reference velocity. Thus it can be seen that a low value of reference velocity should be used in designing a combustion chamber.

Some of the design conditions were dictated by the air source which would be available to test the combustion chamber when built. This source is from the second stage of an Allison V-1710 supercharger and is about three pounds per second at 1.6 atmospheres and 200° F.

As a result of this survey and from consideration of the air source available for testing, the following design point was selected:

Altitude = sea level

w = 3 lb/sec

FIGURE 3
COMBUSTION LOSS VS. COMBUSTION INTENSITY
FOR
LUCAS B-37 CHAMBER.



P_{4T} = 1.6 atmospheres

T_{4T} = 200° F or 660° R

T_{5T} = 1500° F or 1960° R

v_r = 100 ft/sec

M_r = .08

L/D = between 3 and 4

l/D = between 2 and 3.

VI. DESIGN PROCEDURE AND CALCULATIONS

Maximum Diameter of Combustion Chamber

$$v_r = M_r(a)$$

where v_r = reference velocity in ft/sec

M_r = reference Mach number

a = speed of sound in ft/sec = $49\sqrt{T_{4T}}$

where T_{4T} = temperature in °R at entrance to combustion chamber

$$v_r = .08 \times 49\sqrt{660}$$

$$= 100 \text{ ft/sec}$$

$$\rho = \rho_{sc} \times \frac{P_{4T}}{P_{sc}} \times \frac{T_{sc}}{T_{4T}}$$

where ρ = density of air in lb/ft^3

ρ_{sc} = density of air in lb/ft^3 at standard conditions

P_{4T} = total pressure in lb/ft^2 at entrance to combustion chamber

P_{sc} = atmospheric pressure in lb/ft^2 at standard conditions

T_{sc} = temperature in °R at standard conditions

$$\rho = .07651 \times \frac{3380}{2115} \times \frac{520}{660}$$

$$= .0965 \text{ lb/ft}^3$$

$$A = \frac{W}{\rho v_r}$$

where A = area of combustion chamber in ft^2

w = air flow in lb/sec

$$A = \frac{3}{.0965 \times 100}$$

$$= .29 \text{ ft}^2$$

$$D = \sqrt{\frac{A}{.74}}$$

where D_{max} = maximum diameter of combustion chamber in ft

$$D_{max} = \sqrt{\frac{.29}{.783}}$$

$$= .61 \text{ ft} = 7.33 \text{ in}$$

Fuel Required

$$c_{Pave} = \frac{c_{P4} + c_{p5}}{2}$$

where c_{Pave} = average specific heat at constant pressure in Btu/lb air - ^{o}R

c_{P4} = specific heat at constant pressure in Btu/lb air - ^{o}R at entrance to combustion chamber

c_{P5} = specific heat at constant pressure in Btu/lb air - ^{o}R at exit from combustion chamber

$$c_{pave} = \frac{.2403 + .277}{2}$$

$$= .256 \text{ Btu/lb air} - {}^{o}R$$

$$q = c_{Pave} (T_{5T} - T_{4T})$$

where q = heat required in Btu/lb air

T_{5T} = total temperature at combustion chamber exit in ^{o}R

$$q = .256(1960 - 660)$$

$$= 343 \text{ Btu/lb air}$$

$$w_f = \frac{qW}{L.H.V.}$$

where w_f = fuel required in lb/sec

L.H.V. = lower heating value of fuel in Btu/lb

$$w_f = \frac{343 \times 5}{18500}$$

$$= .056 \text{ lb fuel/sec}$$

Primary Air Required

In order to obtain sufficient combustion in the primary zone, there should be a stoichiometric mixture of fuel and air in this zone. Thus, the fuel-air ratio must be .067.

$$w = \frac{w_f}{.067}$$

where w = weight of primary air required in lb/sec

$$w = \frac{.056}{.067}$$

$$= .85 \text{ lb/sec}$$

Volume Available for Combustion

$$V = \frac{q}{HI}$$

where V = volume available for combustion in ft^3

q = heat input in Btu/hr

P = pressure inside chamber in atmospheres

I = combustion intensity factor in Btu/hr-ft^3-atm

$$V = \frac{.056 \times 3600 \times 18500}{1.6 \times 8 \times 10^6}$$

$$= .29 \text{ ft}^3$$

Configuration of Burner Basket

As shown in Figure 4, the burner is made up of three sections---hemisphere or dome, cylinder, and tail cone. Thus,

$$V_T = V_H + V_C + V_{TC}$$

where V_T = total volume in ft^3 = .29 ft^3

V_H = volume of hemisphere in ft^3

V_C = volume of cylinder in ft^3

V_{TC} = volume of tail cone in ft^3

Then,

$$V_T = \frac{\pi D^3}{12} + \frac{\pi D^2 l_C}{4} + \frac{h}{3}\left(\frac{\pi D^2}{4} + \frac{\pi d^2}{4} + \sqrt{\frac{\pi D^2}{4} \times \frac{\pi d^2}{4}}\right)$$

where D = diameter of cylinder in ft

d = smaller diameter of tail cone in ft

l_C = length of cylinder in ft

h = length of tail cone in ft

Assuming that D = 6 in = 1/2 ft, d = 4 in = 1/3 ft, and h = 5 in = 5/12 ft:

$$.29 = \frac{.785}{4} l_C + \frac{.262}{8} + \frac{5}{36}\left(\frac{.785}{4} + \frac{.785}{9} + \sqrt{\frac{.785}{4} \times \frac{.785}{9}}\right)$$



FIGURE 4 SKETCH OF BURNER BASKET, DOME, AND TAIL CONE.

Solving for l_C,

$$l_C = 1.02 \text{ ft} = 12.25 \text{ in}$$

Then,

$$l = l_C + 2.25$$

where l = length from fuel nozzle to downstream end of cylinder in inches

2.25 = length from fuel nozzle to upstream end of cylinder in inches

$$l = 12.25 + 2.25 = 14.5 \text{ in}$$

Also,

$$L = l + h$$

where L = length from fuel nozzle to end of tail cone in inches

$$L = 14.5 + 5 = 19.5 \text{ in}$$

Then,

$$\frac{l}{D} = 2.42 \text{ and } \frac{L}{D} = 3.25$$

Since the values of l/D and L/D are between the desired values of 2 and 3 and 2 to 4 respectively, the dimensions of the burner basket were selected as assumed and calculated in the foregoing procedure and may be summarized as follows:

D = 6 in	l_C = 12.25 in
d = 4 in	l = 14.5 in
h = 5 in	L = 19.5 in

Design of Primary Zone

The problem of introducing the primary air with the proper turbulence is the most important single factor in the design of a combustion chamber, according to A. J. Nerad (Ref. 4). When done properly, a smooth, continuous ignition process occurs in the dome end of the combustion chamber.

Best results have been obtained when everything possible has been done to produce a strong reverse flow in the primary zone. This reverse or "back-flow" produces an "ignition eddy" or "tore," as it is referred to in Nerad's paper.

To establish the existence of this "tore" beyond any doubt, various tests have been carried out with pressure probes, along with other tests such as injecting the fuel into the first ring of holes instead of at the nozzle. These tests have proved that the flow is essentially that which is shown in Figure 5.

Looking at the end view of Figure 5, it is obvious that the eight strong jets of air impacting at the center must produce a substantial axial flow both into and out of the plane of the paper. The axial flow which goes forward is deflected outward by the dome and emerges in the relatively unobstructed areas between the rows of air inlets. This air has mixed with fuel and been ignited and now is "hot burning gases." These gases pass in close proximity to the incoming cold air and part is entrained by it, re-

Duties of Citizens Open





FIGURE 4. CUTAWAY DIAGRAM OF COMBUSTION CHAMBER SHOWING FLOW OF AIR.

sulting in extremely fast preheating of the incoming combustion air. This has a very beneficial effect on good ignition and smooth combustion.

Since it is desirable to have this "back-flow" as strong as possible, all the primary air, except a small amount necessary for cooling and carbon prevention, will be introduced through holes in the basket downstream from the fuel nozzle.

The flow through the combustion chamber is parallel, i.e., the mass of air which enters the combustion chamber through any hole or slot in the burner basket does not in turn pass through any other hole or slot on its way to the turbine, and, likewise, the air which travels through the annular path in the tail cone has not previously passed through any hole or slot in the basket. Since the flow is parallel, the friction pressure drop through any part of the burner must equal that through any other part. This fact was used in designing the combustion chamber.

The design of the primary zone was completed as follows:

First, the weight flow through a ring of eight 1/2 inch primary holes located 4-1/2 inches from the nozzle was determined approximately by the formula:

$$w = \rho A_2 v C_o$$

where w = air flow through the ring of holes in lb/sec

A_2 = area of the holes in ft^2

$$\sqrt{6} \approx \text{the ratio of the volume to } 6\sqrt{2}$$

$$12\sqrt{2}\,a^3$$

where a = the time elapsed for the volume to double

$$= 2^{\frac{1}{6}}\,\text{half-life}$$

and differentiating logarithmically at the beginning

which furnish twelve fivefold 0-1/2 reduces time for volume

Hence, the multiple time elapsed = time at which 1/2

time.

the density of the material does not contribute to lon-

ger and read in centigrade the temperature-

its volume only about five thousandths and twice at

earth', the principles harmonize when pressing and twice at

pressing and still or alter in the one another. Since the time is

consider half in the still seems just two temperature pressure

pressure', and, therefore, the air water increase pressing the

rate have pressing the still water into is the air is the

standing and into or right in the natural instant time one in

1'4', the rates of air right measure the instantaneous change

that needed.

The time pressing the temperature instant in twenty'

International changing inches in the natural acceleration times the

amount necessary the wanting and measure 'pressing' will be

pressed be theories' all the natural pressing a small

Since it is derived to have title 'pressing' be

fluiding and amount accurately.

ance originally Last temperature at the increasing pos-

sation air. This pen a work immediately within or heat

motion is expressed Last temperature at the increasing pos-

ρ = density of air in lb/ft^3

v = velocity of air through holes in ft/sec and is taken as equal to that in the clearance area between the liner and the burner basket

C_o = orifice coefficient

C_o, the orifice coefficient, was obtained from a graph (Ref. 5) after computing Reynold's number and the diameter ratio as follows:

$$A_1 = \frac{\pi}{4}(D_{od}^2 - D_{id}^2)$$

Where A_1 = clearance area between basket and burner shell at the location of the primary holes in ft^2

D_{od} = outside diameter of clearance area in ft

D_{id} = inside diameter of clearance area in ft

$$A_1 = .785\left[\left(\frac{7.25}{12}\right)^2 - \left(\frac{6.1}{12}\right)^2\right]$$

$$= .089 \text{ ft}^2 = 12.8 \text{ in}^2$$

$$D_1 = \sqrt{\frac{A_1}{\pi/4}}$$

Where D_1 = diameter in ft of a pipe with area equivalent to A_1

$$D_1 = \sqrt{\frac{.089}{.785}}$$

$$= .336 \text{ ft} = 4.04 \text{ in}$$

At this point, it is assumed that .25 lb air/sec will have been used previously for cooling and carbon prevention.

$$\text{b.c. density of air in 1b/ft3}$$

$$\text{x = velocity of air through inlet in ft/sec and is}$$

$$\text{number as equal to that in elsewhere once be-}$$

$$\text{tween the floor and the water content}$$

$$\text{E^1 = relative humidity}$$

$$\text{E^1, the relative humidity, was obtained from a}$$

$$\text{psych chart, at other ambient humidity's another may the}$$

$$\text{dimensionless ratio as follows:}$$

$$E^1 = \frac{\pi}{2}(E^1_2 + E^1_1)$$

$$\text{where E^1 = dimensionless mass balance factor and instead}$$

$$\text{equal to the location of the highest}$$

$$\text{value in E^1_2}$$

$$E^1_2 = \text{initial dimension of dimensions such as it}$$

$$E^1_1 = \text{relative dimension of dimensions such as it}$$

$$\text{value in E^1_2}$$

$$\text{Then } E^1 = .785\left[\left(\frac{D^2_{in}}{D^2}\right)_2 - \left(\frac{D^2_{in}}{D^2}\right)_1\right]$$

$$= .785\left[\left(\frac{12.5}{12}\right)^2 - \left(\frac{12.5}{12.5}\right)^2\right]$$

$$= .785\left[1.085 - 1\right]$$

$$= .085$$

$$D^1 = \sqrt{\frac{D^2_{in}}{E^1}}$$

$$\text{where D^1 = diameter in ft of a disc with same}$$

$$\text{equivalent to A^1}$$

$$D^1 = \sqrt{\frac{.785}{.785}}$$

$$\text{will also have been sufficiently low enough not induce tur-}$$

$$\text{bulence for proper flow}$$

$$\text{a = 785 ft = 4704 in}$$

$$v_1 = \frac{w_1}{\rho A_1}$$

where v_1 = velocity in ft/sec through clearance area

w_1 = air flow in clearance area in lb/sec

$$v_1 = \frac{3 - .25}{.0965 \times .089} = 320 \text{ ft/sec}$$

By Sutherland's formula:

$$\mu = \mu_r \left(\frac{T_r + K}{T + K}\right)\left(\frac{T}{T_r}\right)^{3/2}$$

where μ = viscosity of the air in poises

$\mu_r = 170.9 \times 10^{-6}$ poises

$T_r = 273^\circ$ K

K = 120

T = temperature of air = 366.4° K

$$= 170.9 \times 10^{-6} \left(\frac{393}{486.4}\right)\left(\frac{366.4}{273}\right)^{3/2}$$

$$= 2.145 \times 10^{-4} \text{ poises}$$

$$= 2.145 \times 10^{-4} \times 2.09 \times 10^{-3} \text{ slugs/ft-sec}$$

Then, $$NR = \frac{g_1 v_1 \rho}{\mu g}$$

where NR = Reynold's number

g = gravitational constant = 32.2 ft/sec^2

$$\Delta P = \frac{\rho v^2}{2g}$$

where ΔP = velocity in lb/ft^2 through elevation zone

ΔP = pressure drop in elevation zone in lb/ft^2

$$\Delta P = \frac{\text{[illegible]}}{\text{[illegible]}} = \text{[illegible]} \text{ lb/ft}^2$$

[illegible]

$$\dot{m} = \text{[illegible]} \left(\frac{\text{[illegible]}}{\text{[illegible]}}\right)\left(\frac{\text{[illegible]}}{\text{[illegible]}}\right) \text{lb/s}$$

where $\dot{m}$ = mixture[illegible] at the exit in lb/sec

$\dot{m}$ = [illegible]

ΔP = [illegible]

t = [illegible]

L = [illegible] at 40% = [illegible]

$$= \text{[illegible]} = \text{[illegible]} \left(\frac{\text{[illegible]}}{\text{[illegible]}}\right)\left(\frac{\text{[illegible]}}{\text{[illegible]}}\right) \text{lb/s}$$

$$= \text{[illegible]} = \text{[illegible]} \times \text{[illegible]} \text{ [illegible]-sec}$$

$$= \text{[illegible]} = \text{[illegible]} \text{ [illegible]}$$

[illegible]

$$\text{[illegible]} = \frac{\text{[illegible]}}{\text{[illegible]}}$$

where [illegible] = [illegible]

f = [illegible] = [illegible] lb/ft-sec

$$NR = \frac{.336 \times 320 \times .0965}{.45 \times 10^{-6} \times 32.2}$$

$$= .716 \times 10^6$$

$$A_2 = \frac{\pi}{4} N_h D_h^2$$

where N_h = number of holes in ring

D_h = diameter of each hole in ft

$$A_2 = .785 \times 8 \times \left(\frac{1/2}{12}\right)^2$$

$$= .011 \text{ ft}^2 = 1.56 \text{ in}^2$$

$$\frac{D_2}{D_1} = \sqrt{\frac{A_2}{A_1}} = \sqrt{\frac{1.56}{12.8}} = .35$$

Then, with these values of NR and D_2/D_1 and the chart of Reference 5, we find C_o = .61.

Thus,

$$w = .0965 \times .011 \times 320 \times .61$$

$$= .2 \text{ lb/sec}$$

$$Q = \frac{w}{\rho}$$

where Q = air flow through ring of holes in ft^3/sec

$$Q = \frac{.2}{.0965} = 2.07 \text{ ft}^3/\text{sec}$$

The friction pressure drop was then calculated by the following formula from Reference 6:

$$\Delta P = \frac{\rho}{2g}\left[\frac{Q}{A_2 C_o\sqrt{1-\left(\frac{A_2}{A_1}\right)^2}}\right]^2$$

where ΔP = friction pressure drop in lb/ft^2

$$\Delta P = \frac{.0965}{2 \times 32.2}\left[\frac{2.07}{.011 \times .61\sqrt{1-\left(\frac{.011}{.089}\right)^2}}\right]^2$$

$$= 147\ lb/ft^2 = 1.02\ lb/in^2$$

Since this was considered to be a reasonable value for friction pressure drop, it was selected as the value to be used in designing the combustion chamber.

As previously stated, it was assumed that .25 lb air/sec had been used for cooling and carbon prevention. It was decided that the air to cool the dome should be introduced through a ring of eight 3/8-inch holes around the fuel nozzle. The air jets through these holes impinge on slanted vanes which give them a swirling action and direct them onto the dome. The pressure drop equation was used to determine whether the eight 3/8-inch holes would give the required air flow.

$$Q = \frac{A_2 C_o}{\sqrt{1-\left(\frac{A_2}{A_1}\right)^2}}\sqrt{2g\left(\frac{\Delta P}{\rho}\right)}$$

where Q = air flow through the eight 3/8-inch holes in ft^3/sec

A_2 = area of the eight 3/8-inch holes in ft^2

A_1 = area of combustion chamber in ft^2

$$A_2 = 8 \times \frac{\pi}{4}\left(\frac{3/8}{12}\right)^2 = .00615\ ft^2 = .885\ in^2$$

$$\Delta P = \frac{\rho}{2}\left[\frac{}{}\right]\left[1 + \left(\frac{}{}\right)\right]$$

where ΔP = pressure gradient along an inlet;

$$\Delta = \frac{}{}\left[\left(\frac{}{}\right) - 1\right]\left[\frac{}{}\right]$$

ρ = air density = 1.225 kg/m^3

Since this was considered to be a reasonably value for filtering purposes only, it was assumed to be valid in using in Equation the manufacturer's chart.

As previously stated, it was assumed that 70% of air would be deviated after passing and medium (screen). It was decided that air be used for testing and medium in order to simplify matter. The air jets supplied three noise problems in normal ducted ventilation - flow at right (1/8-inch) inches measured the two screen which gave them a vertical motion and direct flow onto the floor. The propeller type exhaust fan used in operation of the filter would give the required air flow.

$$= \frac{}{\sqrt{1 - \left(\frac{}{}\right)^2}}\left(\frac{\Delta}{\rho}\right)$$

where ϵ = air flow through the right 1/8-inch holes in inches

A_p = area of the right 1/8-inch holes in ft^2

A^p = area of ventilation chamber in ft^2

$$A_p = \frac{\pi}{4}\left(\frac{}{}\right) = .0077 \text{ ft}^2 = .109 \text{ in}^2$$

$$A_1 = \frac{\pi}{4}\frac{7.33}{12}^2 = .89 \text{ ft}^2 = 41.8 \text{ in}^2$$

$$Q = \frac{.00615 \times .61}{\sqrt{1 - \left(\frac{.00615}{.89}\right)^2}}\sqrt{64.4\left(\frac{147}{.0965}\right)}$$

$$= 1.17 \text{ ft}^3/\text{sec or } .11 \text{ lb/sec}$$

This value seems reasonable since a portion of the .25 lb air/sec must enter through an annular slot located between the nose hemisphere and the walls of the basket. The desired flow through this slot is then:

$$.25 - .11 = .14 \text{ lb/sec or } 1.45 \text{ ft}^3/\text{sec}$$

The pressure drop equation was used to find the slot area required to obtain this flow. Since the term $\sqrt{1 - (A_2/A_1)^2}$ will be very nearly equal to 1, the pressure drop equation may be used to solve for A_2 thus:

$$A_2 = \frac{Q}{C_c\sqrt{2g\left(\frac{\Delta P}{\rho}\right)}}$$

where A_2 = slot area in ft^2

Q = air flow through the slot in ft^3/sec

$$A_2 = \frac{1.45}{.61\sqrt{64.4\left(\frac{147}{.0965}\right)}}$$

$$= .0076 \text{ ft}^2 = 1.09 \text{ in}^2$$

The required thickness of the slot is found as follows:

$$A_2 = \frac{\pi}{4}\left[D^2 - (D - x)^2\right]$$

where D = diameter of burner basket in inches

x = clearance in inches

$$1.09 = \frac{\pi}{4}\left[36 - (6 - x)^2\right]$$

$$x = .116 \text{ in}$$

The slot thickness will then be:

$$\frac{X}{2} = \frac{.116}{2} = .058 \text{ in} \approx 1/16 \text{ in}$$

In order to get the required air flow for the primary section, three rings of eight 1/2-inch holes were required in the burner basket in addition to the ring of eight 3/8-inch holes in the dome and the annular slot.

Design of Secondary Zone

The weight flow through the primary zone is .85 lb/sec. This leaves 2.15 lb/sec to flow through the secondary zone which includes cooling louvres, the tail cone annulus, and the secondary holes.

Louvres

Air introduced through the louvres is intended to cool the basket and to prevent the formation of carbon. The louvres are shaped to deflect the air along the inner surface of the liner, thus keeping the velocity high enough to sweep away any carbon which might form. Three rings of eight louvres each were considered adequate.

Each louvre is 1/2 inch long and 1/16 inch deep. This gives an area of:

$$A = \frac{1}{16} \times \frac{1}{2} = .0312 \text{ in}^2$$

The area of one ring of eight louvres is:

$$A = .0312 \times 8 = .25 \text{ in}^2$$

Now, assuming an orifice coefficient of .61, the flow through the louvres is as follows:

$$Q = A_2 C_o \sqrt{2g\left(\frac{\Delta P}{\rho}\right)}$$

(The term $1/\sqrt{1 - (A_2/A_1)^2}$ has been omitted since in all cases it is very nearly equal to 1.)

$$\text{where } Q = \frac{.25}{144} \times .61 \sqrt{64.4 \left(\frac{147}{.0965}\right)}$$

$$= .332 \text{ ft}^3/\text{sec or } .032 \text{ lb/sec}$$

For three rings, the flow will be:

$$3 \times .032 = .096 \text{ lb/sec}$$

Tail Cone Annulus

The flow through the tail cone annulus is necessary to cool the inner liner which is in direct contact with the hot gases. The film of air need not be very large to accomplish this. The 1/16-inch clearance allowed is in accordance with current practice.

According to Reference 7, the pressure drop across the tail cone annulus is given by the following formula:

$$\frac{\Delta P}{\rho} = \frac{f}{4} \frac{h}{R} \frac{v^2}{2g}$$

where ΔP = friction pressure drop in lb/ft^2 = 147 lb/ft^2

ρ = density of air in lb/ft^3 = .0965 lb/ft^3

f = friction factor

h = length of tail cone in ft = 5/12 ft

R = hydraulic radius in ft

v = average velocity through annular space in ft/sec

Reference 8 gives the relation between f and Reynold's number, NR. NR, in turn, is dependent upon v. Thus, it can be seen that a cut and try calculation is necessary to arrive at values of f and v which will satisfy the above equation. From Reference 7,

$$NR = \frac{4v\rho R}{\mu g}$$

where μ = viscosity in slugs/ft-sec

$$R = \frac{A_{ave}}{WP}$$

Where A_{ave} = average cross-sectional area in ft^2

WP = wetted perimeter in ft

$$A_{ave} = .785\left[\frac{[(6.125)^2 - 6^2] + [(4.125)^2 - 4^2]}{2}\right]$$

$$= 1.023 \text{ in}^2 = .00711 \text{ ft}^2$$

$$WP = \pi\left(D_2 + D_1\right)$$

where D_1 = inside diameter of section at A_{ave} in ft

D_2 = outside diameter of section at A_{ave} in ft

$$D_2 = D_1 + \frac{.125}{12}$$

$$.00711 = .785\left[\left(D_1 + \frac{.125}{12}\right)^2 - D_1^2\right]$$

$$D_1 = .43 \text{ ft}$$

$$D_2 = .44 \text{ ft}$$

$$WP = \pi(.43 + .44) = 2.735 \text{ ft}$$

$$R = \frac{.00711}{2.735} = .0026 \text{ ft}$$

Assuming v = 250 ft/sec:

$$NR = \frac{4 \times 250 \times .0965 \times .0026}{.45 \times 10^{-6} \times 32.2}$$

$$= 17320$$

and f = .042

Solving for v to check assumption:

$$\frac{147}{.0965} = \frac{.042}{4}\left(\frac{5/12}{.0026}\right)\frac{v^2}{64.4}$$

$$v = 242 \text{ ft/sec}$$

Assuming v = 240 ft/sec and recalculating:

$$NR = 17320 \times \frac{240}{250} = 13860$$

and f = .0435

$$v = 242\sqrt{\frac{.042}{.0435}} = 238 \text{ ft/sec}$$

This checks the assumed value. Then,

$$Q = A_{ave}\, v$$

where Q = flow through tail cone annulus in ft^3/sec

$$Q = .00711 \times 240$$

$$= 1.707 \text{ } ft^3/sec \text{ or } .165 \text{ lb/sec}$$

Secondary Holes

Knowing the flow through the primary zone, the louvres, and the tail cone annulus, the weight flow through the secondary holes can be obtained.

.85 lb/sec primary air

.165 lb/sec tail cone annulus

.096 lb/sec louvres

1.111 lb/sec total

Then, the weight flow through the secondary holes is

3.000 - 1.111 = 1.889 lb/sec

Because of the high velocities in the combustion chamber, it was assumed that the air would flow through the secondary holes at some angle other than 90°. This angle was taken to be 45° throughout the secondary zone. Appendix A presents an experiment which was the basis for this assumption.

This angularity of flow necessitates the introduction of an effectiveness coefficient, C_e, in addition to the orifice coefficient, C_o, when calculating flow through

a secondary hole. C_e is defined as the sine of the angle of flow.

$$C_e = \sin 45^\circ$$

$$= .707$$

To find the flow through a ring of eight 5/8-inch secondary holes:

$$Q = N_h A_2 C_e C_o \sqrt{2g\left(\frac{\Delta P}{\rho}\right)}$$

where Q = air flow through ring of holes in ft^3/sec

N_h = number of holes in ring = 8

A_2 = area of each hole = .00213 ft^2

C_e = effectiveness coefficient = .707

C_o = orifice coefficient = .61

g = gravitational constant = 32.2 ft/sec^2

ΔP = friction pressure drop = 147 lb/ft^2

ρ = density of air = .0965 lb/ft^3

$$Q = 8 \times .00213 \times .707 \times .61 \sqrt{64.4 \left(\frac{147}{.0965}\right)}$$

$$= 2.29 \text{ ft}^3/\text{sec or } .221 \text{ lb/sec}$$

Similarly, for a ring of eight 11/16-inch holes is 2.88 ft^3/sec or .278 lb/sec. Thus, six rings of 11/16-inch holes and one ring of 5/8-inch holes will admit the 1.889 lb/sec of secondary air that remains.

Check of Air Flows

	.11	lb/sec	holes in hemisphere
	.14	"	annular slot
3 x .2 =	.60	"	three rings of 1/2-inch holes
6 x .278 =	1.67	"	six rings of 11/16-inch holes
	.221	"	one ring of 5/8-inch holes
	.165	"	tail cone annulus
	.096	"	louvres
	3.002	lb/sec	total air flow check

Location of Holes

The primary air should be introduced far enough downstream to insure the development of a strong combustion eddy. This is about three-fourths to one diameter from the fuel nozzle.

The secondary air should be first introduced at a low rate and then at an increasingly greater rate downstream. This is to prevent chilling of the flame front and the resulting stoppage of the combustion process. By introducing the first part of the secondary air six to eight inches from the fuel nozzle, enough time is allowed for the combustion to be well along towards completion.

A convenient method for locating the primary and secondary holes to satisfy these requirements is shown in Figure 6 in which total area of the openings into the basket

Cost of the Plane

Wood		.05
Steel		.15
Fabric		.10
Engine		.25
Propeller		.05
Instruments		.10
Miscellaneous		.05
Total direct cost of plane		$ .75

Operation of Plane

The primary air should be introduced for economy considerations to increase the horsepower of a stroke engine. This is since three-fourths of the air comes from the fuel mixture.

The recommended air density is three pounds per hour per ton of thrust at the static thrust and cruise. This is an average obtained at the flight speed and the thrust horsepower. If before the airplane reaches the top of the ascent, enough time is allowed for the engine cools the fuel should, enough time is allowed for the propeller to be used because the propeller.

A mechanical method for inducing the primary and secondary joint is easily those modifications be shown in Figure 1 is noted right when of the planning into the boat.



FIGURE 6
CURVE USED IN LOCATING PRIMARY AND SECONDARY HOLES.

is plotted vs. distance from the fuel nozzle. The curve shown in an arc of a circle and is defined as follows:

1. The center of the circle lies on the vertical line through the zero distance point.
2. One point on the arc is the area of the openings into the burner basket ahead of the fuel nozzle, i.e., the area of the eight 3/8-inch holes. This area is plotted at the point of zero distance.
3. The other point of the arc is the total area of all the openings, slots, and louvres in the burner basket. This area is plotted at the distance at which the last row of secondary holes is desired.

Now, by taking the areas of the rings of holes and fitting them to this curve, a satisfactory distribution will automatically follow.

This method, used judiciously, should take much of the cut and try out of burner design.

The cooling louvres can now be placed in spots where the boundary layer would otherwise thicken up and let carbon deposits form.

Figure 7 shows the final configuration of the combustion chamber.

time elsewhere.

Effect 1 proves the first exclusivity of the boundary-
determined form.

The Permitted Index method represents an early but crucial
step away from the use of implicit semantics.

This section' then Initialized' objects these ways of
exceptionally Define.

time to this source.' A multinational distribution will main-
tain" be creating the access of the client to solve the Extend
to operation.

   changes or noting the Task are it meaningful point
   Indian Income'. This case is starting at the Che-
   nyl and Chemistry' objects' may increase in the
   reason.

   This object factor of the end in the input case of
   t**.' the name is the right Information input.
   into the Partial Income' object of the Last country'
   Time Current the case Statement right.

c. Use Index as the Circle Tion as the variant
   Be floated in. Standard from the Last country. The curve
   elsewhere in the case of a study and to Deficient in Position



FIGURE 7 DESIGNED COMBUSTION CHAMBER.

FULL SCALE

VII. CALCULATION OF PERFORMANCE

Friction Pressure Drop

Since the flow through the combustion chamber is parallel, the pressure drop through any one part is equal to the pressure drop through the entire burner. The friction pressure drop, as calculated in the preceding section, is:

$$\Delta P = 147 \text{ lb/ft}^2 \quad \text{or} \quad 1.02 \text{ lb/in}^2$$

Momentum Pressure Drop

Having the friction pressure loss in hand, it is now necessary to determine the pressure loss due to combustion in order to have the total pressure loss through the burner.

The assumption is now made that the combustion takes place in a burner of constant cross-sectional area and that no mass is added by the fuel.

In a combustion process, the impulse-momentum law holds. This law states that "impulse is equal to the change in momentum." Written mathematically, this is:

$$Ft = \Delta (Mv)$$

where F = pounds force

t = time in sec

M = pounds mass

v = velocity in ft/sec

VII. Conclusion

Finding Pressure Loss

Since the flow through the accumulation chamber is parallel, the pressure drop through any one path is equal to the pressure drop through the entire chamber. The friction pressure drop, as calculated in the preceding section, is

$$\Delta P = 147.1 \text{ lb/ft}^2 \text{ or } 1.02 \text{ lb/in}^2$$

Sizing the Friction Screen

Having the friction pressure loss in hand, it is now necessary to determine the pressure loss due to accumulation in order to know the total pressure loss through the barrier.

The assumption is now made that the combination tubing is a vacuum of constant cross-sectional area and that no water is added by the flow.

In a combination process, the impulse-conservation law holds. This law states that "Impulse is equal to the change in momentum." Written mathematically, this is:

$$Ft = \Delta (mv)$$

where F = pounds force

t = time in sec

m = pounds mass

v = velocity in ft/sec

Now, since mass is assumed constant:

$$Ft = M\Delta v$$

$$F = \frac{M}{t}\Delta v$$

$$F = \frac{w}{g}(v_5 - v_4)$$

where w = weight flow in lb/sec

g = ratio of absolute to gravitational units of mass

Pressure is force per unit area, and since the burner is of constant area,

$$AP_{4s} - AP_{5s} = \frac{w}{g}(v_5 - v_4)$$

where P_{4s} = entering static pressure in lb/ft^2

P_{5s} = exit static pressure in lb/ft^2

A = burner area in ft^2

In the burner at hand, the known conditions are: entering total pressure, P_{4t}; entering velocity, v_4; entering total temperature, T_{4t}; and exit total temperature, T_{5t}. In order to obtain pressure drop due to combustion, it is necessary to know the theoretical exit total pressure, P_{5t}.

From adiabatic considerations, it is known that:

$$\frac{P_{4t}}{P_{4s}} = \left(\frac{T_{4t}}{T_{4s}}\right)^{\frac{\gamma}{\gamma-1}}$$

and

$$\frac{P_{5t}}{P_{5s}} = \left(\frac{T_{5t}}{T_{5s}}\right)^{\frac{\gamma}{\gamma-1}}$$

$$\frac{dv}{dr} = \left(\frac{2m}{L^2}\right)^{\frac{1}{\lambda}-1}$$

$$\frac{dv}{dr} = \left(\frac{2m}{L^2 r^2}\right)^{\frac{1}{\lambda}-1}$$

Then, $$\frac{P_{5t}}{P_{4t}} = \frac{P_{5s}}{P_{4s}}\left(\frac{T_{5t}}{T_{4t}}\right)^{\frac{\gamma}{\gamma-1}}\left(\frac{T_{4s}}{T_{5s}}\right)^{\frac{\gamma}{\gamma-1}}$$

Since $$P/\rho = RT$$

where P = pressure in lb/ft^2

ρ = density in lb/ft^3

R = gas constant in $ft/^oR$

T = temperature in ^oR

and $$Q = w/\rho$$

where Q = volume flow in ft^3/sec

then $$\frac{PQ}{w} = RT$$

and $$\frac{P_{4s}Q_4}{T_{4s}} = Rw = \frac{P_{5s}Q_5}{T_{5s}}$$

Also, $$\frac{P_{4s}v_4}{T_{4s}} = \frac{P_{5s}v_5}{T_{5s}}$$

So, $$\frac{P_{5t}}{P_{4t}} = \frac{v_4}{v_5}\left(\frac{T_{5t}}{T_{4t}}\right)^{\frac{\gamma}{\gamma-1}}\left(\frac{T_{4s}}{T_{5s}}\right)^{\frac{\gamma}{\gamma-1}}$$

To find static temperatures:

$$\frac{T_{4t}}{T_{4s}} = 1 + \frac{\gamma-1}{2}M_4^2$$

and $$M_4^2 = \frac{v_4^2}{\gamma g R T_{4s}}$$

$$\frac{T_{4t}}{T_{4s}} = 1 + \frac{\gamma - 1}{2}\left(\frac{v_4^2}{\gamma g R T_{4s}}\right)$$

$$T_{4t} = T_{4s} + \frac{\gamma - 1}{2}\left(\frac{v_4^2}{\gamma g R}\right)$$

Then, $$T_{4s} = T_{4t} - \frac{v_4^2}{2gR\left(\frac{\gamma}{\gamma - 1}\right)}$$

Similarly, T_{5s} is obtained.

To find v_5:

$$AP_{4s} - AP_{5s} = \frac{w}{g}(v_5 - v_4)$$

$$A = Q/v$$

$$\frac{P_{4s}Q_4}{v_4} - \frac{P_{5s}Q_5}{v_5} = \frac{w}{g}(v_5 - v_4)$$

$$P/\rho = RT$$

$$Q = w/\rho$$

$$PQ = RTw$$

Now, $$\frac{RT_{4s}w}{v_4} - \frac{RT_{5s}w}{v_5} = \frac{w}{g}(v_5 - v_4)$$

$$\frac{T_{4s}}{v_4} - \frac{T_{5s}}{v_5} = \frac{1}{Rg}(v_5 - v_4)$$

$$\frac{T_{4s}}{v_4} = \frac{T_{4t}}{v_4} - \frac{v_4}{2gR\left(\frac{\gamma}{\gamma - 1}\right)}$$

$$\frac{T_{5s}}{v_5} = \frac{T_{5t}}{v_5} - \frac{v_5}{2gR\left(\frac{\gamma}{\gamma - 1}\right)}$$

$$\frac{T_{4s}}{v_4} - \frac{T_{5s}}{v_5} = \frac{T_{4t}}{v_4} - \frac{T_{5t}}{v_5} + \frac{v_5 - v_4}{2gR\left(\frac{\gamma}{\gamma - 1}\right)}$$

$$\frac{T_{4t}}{v_4} - \frac{T_{5t}}{v_5} + \frac{v_5 - v_4}{2gR\left(\frac{\gamma}{\gamma - 1}\right)} = \frac{1}{Rg}(v_5 - v_4)$$

$$\frac{T_{4t}}{v_4} - \frac{T_{5t}}{v_5} = \frac{1}{Rg}(v_5 - v_4) - \frac{v_5 - v_4}{2gR\left(\frac{\gamma}{\gamma - 1}\right)}$$

$$= (v_5 - v_4)\left[\frac{1}{Rg} - \frac{1}{2gR\left(\frac{\gamma}{\gamma - 1}\right)}\right]$$

$$= (v_5 - v_4)\left[\frac{2\gamma - (\gamma - 1)}{2\gamma gR}\right]$$

$$= (v_5 - v_4)\left(\frac{\gamma + 1}{2\gamma gR}\right)$$

$$\frac{T_{4t}}{v_4}\left[1 - \frac{T_{5t}/v_5}{T_{4t}/v_4}\right] = \left(\frac{\gamma - 1}{2\gamma gR}\right) v_4 \left(\frac{v_5}{v_4} - 1\right)$$

$$\frac{T_{4t}}{v_4}\left[1 - \frac{T_{5t}}{T_{4t}}\frac{v_4}{v_5}\right] = \left(\frac{\gamma + 1}{2\gamma gR}\right) v_4 \left(\frac{v_5}{v_4} - 1\right)$$

$$1 - \frac{T_{5t}}{T_{4t}} \frac{v_4}{v_5} = \left(\frac{\gamma + 1}{2}\right)\left(\frac{v_4^2}{\gamma g R T_{4t}}\right)\left(\frac{v_5}{v_4} - 1\right)$$

$$= \left(\frac{\gamma + 1}{2}\right) M_{4t}^2 \left(\frac{v_5}{v_4} - 1\right)$$

$$= \left(\frac{\gamma + 1}{2}\right) M_{4t}^2 \left(\frac{v_5}{v_4}\right) - \left(\frac{\gamma + 1}{2}\right) M_{4t}^2$$

$$1 + \left(\frac{\gamma + 1}{2}\right) M_{4t}^2 = \left(\frac{\gamma + 1}{2}\right) M_{4t}^2 \left(\frac{v_5}{v_4}\right) + \frac{T_{5t}/T_{4t}}{v_5/v_4}$$

$$(v_5/v_4)^2 \left(\frac{\gamma + 1}{2}\right) M_{4t}^2 - \frac{v_5}{v_4}\left[1 + \left(\frac{\gamma + 1}{2}\right) M_{4t}^2\right] + \frac{T_{5t}}{T_{4t}} = 0$$

let $\quad a = \frac{\gamma + 1}{2} M_{4t}^2 \quad$ and $\quad b = \frac{T_{5t}}{T_{4t}}$

$$a\left(\frac{v_5}{v_4}\right)^2 - (1 + a) \frac{v_5}{v_4} + b = 0$$

$$\frac{v_5}{v_4} = \frac{1 + a \pm \sqrt{(1 + a)^2 - 4ab}}{2a}$$

then,

$$\frac{v_5}{v_4} = \frac{1 + \frac{\gamma + 1}{2} M_{4t}^2 \pm \sqrt{1 + \frac{\gamma + 1}{2} M_{4t}^2}^2 - 4\left(\frac{\gamma + 1}{2} M_{4t}^2\right)\frac{T_{5t}}{T_{4t}}}{(\gamma + 1) M_{4t}^2}$$

Substituting the following values in the formula derived for v_5:

$v_4 = 100$ ft/sec $\qquad M_{4t} = .0794$

$\gamma = 1.4 \qquad M_{4t}^2 = .0063$

$\gamma + 1 = 2.4 \qquad \frac{T_{5t}}{T_{4t}} = \frac{1960}{660} = 2.97$

$\frac{\gamma + 1}{2} = 1.2$

we find,

$$\frac{v_5}{100} = \frac{1 + 1.2(.0063) \pm \sqrt{[1 + 1.2(.0063)]^2 - 4(1.2)(.0063)2.97}}{2.4(.0063}$$

$$v_5 = 302 \text{ ft/sec}$$

Substituting the following values in the formulas derived for T_{4s} and T_{5s}:

$v_4 = 100$ ft/sec $\qquad v_5 = 302$ ft/sec

$g = 32.2$ ft/sec^2 $\qquad \gamma = 1.4$

$T_{4t} = 660^\circ$ R $\qquad T_{5t} = 1960^\circ$ R

$R = 53.3$ ft/$^\circ$R

we find,

$$T_{4s} = 660 - \frac{(100)^2}{2(32.2)\left(\frac{1.4}{1.4 - 1}\right)53.3}$$

$$= 659.2^\circ \text{ R}$$

and $$T_{5s} = 1960 - \frac{(302)^2}{2(32.2)\left(\frac{1.4}{1.4 - 1}\right)53.3}$$

$$= 1952.4^\circ \text{ R}$$

Ans:

Substituting the following values in the formula derived for P_{5t}:

$P_{4t} = 1.6$ atm $\qquad \gamma = 1.4$

$v_4 = 100$ ft/sec $\qquad v_5 = 302$ ft/sec

$T_{4t} = 660^\circ$ R $\qquad T_{5t} = 1960^\circ$ R

$T_{4s} = 659.2^\circ$ R $\qquad T_{5s} = 1952.4^\circ$ R

we find,

$$\frac{P_{5t}}{1.6} = \frac{\left(\frac{100}{302}\right)\left(\frac{1960}{660}\right)^{\frac{1.4}{1.4-1}}}{\left(\frac{1952.4}{659.2}\right)^{\frac{1}{1.4-1}}}$$

$$P_{5t} = 1.52 \text{ atm}$$

Then, the momentum pressure drop is:

$$\Delta P = P_{4t} - P_{5t}$$

$$= 1.6 - 1.52$$

$$= .08 \text{ atm} = 1.175 \text{ lb/in}^2$$

Total Pressure Drop

The total pressure drop is the sum of the friction pressure drop and the momentum pressure drop.

Friction pressure drop = 1.02 lb/in^2

Momentum pressure drop = 1.175 lb/in^2

Total pressure drop = 2.195 lb/in^2

Determining the Optimum Values for the Control Variables

For Type1

T_{ff} = 1.6 sec γ = 1.6

d_f = 110 ft/sec M = 800 ft/sec

T_{ff} = 80sec T_{ff} = 1000sec

T_{ff} = 800.6 ft T_{ff} = 1000.4 ft

as Then,

$$\frac{C_{ff}}{C_{ff}} = \frac{\left(\frac{1000}{1000}\right)^{1.6-1}}{\left(\frac{800.6}{1000.4}\right)^{\frac{1}{1.6-1}}}$$

C_{ff} = 1.00 sec

Then, the minimum increased duty for

$$\Delta = C_{ff} - C_{ff}$$

= 1.0 - 1.00

= .00 sec = 1.15 ft/ft$_2$

Other Possible Case

The optimal solution must be the one of the following

Locations must not be considered because

Solution Increase duty = 7.00 ft/ft$_2$

Initial Increase duty = 7.00 ft/ft$_2$

Total Increase duty = 14.00 ft/ft$_2$

For ease in comparing burners of various sizes and capacities, the parameter $\Delta P/P_{4t}$ is used. This value usually lies between four per cent and seven per cent.

$$\frac{\Delta P}{P_{4t}} = \frac{2.195}{1.6 \times 14.7} = .0934 \text{ or } 9.34\%$$

This value is a little high but is explained by the very low value of P_{4t}.

Reference 3 states that the total pressure drop should be in the neighborhood of 20 to 30 times the value of the velocity head q at point 4.

$$q = \frac{\rho v^2}{2g}$$

$$= \frac{.0965(100)^2}{64.4}$$

$$= 15 \text{ lb/ft}^2 \text{ or } .104 \text{ lb/in}^2$$

$$\frac{\Delta P}{q} = \frac{2.195}{.104} = 21.1$$

Thus it is seen that the pressure drop obtained is in accord with Reference 3.

Combustion Efficiency

In an unpublished paper, Mr. W. R. Hawthorne, in collaboration with Professor H. C. Hottel of the Massachusetts Institute of Technology, presented an empir-

ical formula for combustion efficiency. This formula was derived from curves of a series of combustion chambers showing the correlation between combustion efficiency, heat input, and diameter of chamber. The formula is as follows:

$$1 - \eta = e^{\frac{-6 \times 10^6}{ID}}$$

where η = combustion efficiency

e = natural log base = 2.718

I = combustion intensity in Btu/hr-ft^3-atm

D = diameter of combustion chamber in ft

$$1 - \eta = (2.718)^{\frac{-6 \times 10^6}{8 \times 10^6 \times .61}}$$

$$= (2.718)^{-1.235}$$

$$= \frac{1}{3.44} = .2905$$

$$\eta = 1 - .2905$$

$$= .7095 \text{ or } 70.95\%$$

This is a low combustion efficiency. However, this can be attributed to the fact that the very low value of P_{4t} necessitates a very high combustion intensity. The effect of combustion intensity can be shown by substituting an intensity of 4×10^6 Btu/hr-ft^3-atm in the empirical formula. In this case, the efficiency jumps to 92%. In order to obtain a combustion intensity of 4×10^6, P_{4t} must equal 3.2 atmospheres. Even this value of P_{4t} is considered quite low for modern turbo-jet engines.

VIII. CONCLUSIONS

The combustion chamber resulting from this design shows a total pressure drop of 2.195 lb/in^2. G. Geoffrey Smith in Reference 9 states that several standard turbojet engines have combustion chambers which operate with a total pressure drop of about 2 lb/in^2. From this, it would seem that the pressure drop for the designed combustion chamber was not excessive.

The British use pressure drop divided by reference velocity head ($\Delta P/q$) as a parameter for comparing different combustion chambers. Values of this parameter from 20 to 30 are considered reasonable. Here again, the designed combustion chamber conforms, having a $\Delta P/q$ of 21.1.

Another parameter is pressure drop divided by total inlet pressure ($\Delta P/P_{4t}$). Most values of this parameter quoted for standard combustion chambers varied from three to six per cent. However, these values were invariably for total inlet pressures of 3.5 to 4.5 atmospheres. A test of a DeHavilland H-1 combustion chamber, operating at an inlet pressure of 1.8 atmospheres (a value very near the design point of 1.6 atmospheres), showed a $\Delta P/P_{4t}$ of 18%. Thus, it would appear that the value of 9.34% calculated for the designed chamber is acceptable.

Hawthorne's empirical formula for combustion efficiency was given with no indication as to its valid range.

It may be that using this formula under a condition of low inlet pressure is not justified and that actual tests of the chamber would prove the value of 70.95% obtained from it to be much too low a value of combustion efficiency. This would appear to be the case, judging by the results obtained in the aforementioned test of the DeHavilland chamber. Operating under conditions very close to the design point used in this investigation, an efficiency of 94% was obtained.

It is regrettable that time did not permit the building and testing of the design. Only with the test results in hand can it be said positively that the design is good or bad. However, by comparison with proved designs, it would appear to be a satisfactory combustion chamber.

APPENDIX A

OBSERVATION OF FLOW THROUGH SECONDARY HOLES OF TURBO-JET COMBUSTION CHAMBER

Summary

In order to observe the angularity of flow through the secondary holes of a burner basket, a test box was constructed with entrance, exit, and hole areas similar to those in the combustion chamber of a J-33 turbo-jet engine. The J-33 chamber was selected since it was found to be the most nearly similar to the burner designed in this investigation.

Tufts were suspended from the centers of the holes, and the angle of flow was taken as the angle measured between the tufts and the plate containing the holes during passage of an air stream through the test box.

An attempt to read the flow angle by introducing smoke into the air stream was a failure due to the high velocity and the large amount of turbulence present.

It was concluded that, while the angle of flow varied with distance from the fuel nozzle, an average angle of 45° could be used in determining the area of the secondary holes.

Introduction

If the flow through a hole is at an angle other than 90°, the area allowing fluid to pass will not be the ob-

APPENDIX V

CORRELATION OF TWO INDEPENDENT ANALYSES

OF MINOR-CLIF DISTRICT CHARGES

Introduction

It was first thought a task in at an early stage that con-
siderable light would be thrown on the problem of the inception-
ary period.

It was accordingly felt, while the origin of these
variously and the large records of voluntary workers
might into the air stream a factory due to the rain
prevented it an air stream through its back door.

In attempt to read the flow paths by introducing
paper into the rain stream and the white membrane the initial period
at an air stream through its back door.

Paths were suggested from the presence of the white,
and the paths of flow are shown on the white membrane be-
tween the built and the white membrane the initial period
at an air stream through its back door.

It was accordingly felt, while the origin of these
variously and the large records of voluntary workers
of 45° should be used to superimpose the paths of the inception-
ary period.

It was accordingly felt, while the origin of these
variously and the large records of voluntary workers
of 45° should be used to superimpose the paths of the inception-
ary period.

served area of the hole but the projection of the area on the plane perpendicular to the flow. The formula for flow through an orifice is derived for a flow perpendicular to the orifice. When the flow is not perpendicular to the orifice, the projected area must be used in order for the orifice formula to be valid.

The projected area is

$$A = A_h \sin \Theta$$

where A = projected area

A_h = area of hole

Θ = angle of flow

In this paper, $\sin \Theta$ is called C_e, effectiveness coefficient.

Equipment

Figures 8 and 9 show general views of the equipment used in the experiment. In these figures, the parts are numbered as follows:

(1) Eight-inch pipe carrying the flow from the rotary compressor located in the basement.

(2) Water manometer connected to pitot-static tube in the pipe.

(3) Compressed air line.

(4) Smoke generator.

(5) Test box.

Figure 10 shows a close-up of the smoke generator.



Figure 8. Photograph of Test Setup for Observing Angle of Flow.



Figure 9. Another View of the Test Setup for Observing Angle of Flow.

Figure 10. Close-up View of Smoke Generator.

Titanuim tetra-chloride ($TiCl_4$) was placed in the gallon can to produce smoke. The amount of smoke was regulated by a valve in the high pressure air line.

Figure 11, a close-up of the test box, shows the window and the lights used in taking pictures of the flow. The test box itself was designed to simulate conditions in a J-33 burner. Its length was the same as the length of the J-33 burner basket. The plate with the holes in it was placed in such a way that it divided the inlet of the box into two areas: one area equal to the clearance area between the outer shell and the burner basket and the other area equal to the area of the holes around the fuel nozzle plus the area of the annular space between the nose hemisphere and the burner basket. In this manner, approximately correct proportions of the flow were introduced on each side of the plate. At the exit to the test box, the plate again divided the flow. The small area at the exit was made equal to the area between the inner and outer walls of the tail cone. The plate was made with the same size and number of holes as the burner basket.

Fine wire was glued across representative holes in the plate and silk thread tied loosely to it. These silk tufts alined themselves with the flow, making it possible to measure the flow angle.

Procedure

The compressor was started, and, when the flow had

Conclusion

The conclusion was rushed, only when the film ran
to overrun the film length.

Jane grew tired of trying to the Professor laughed.
Then with one final desperate exclamation Anita in
the flame and still burned that instead he it. Jane with
Jane grew tired of trying to the Professor laughed.
Then with one final desperate exclamation Anita in
middle of the tall stone. The flame was made with the same
were made almost at the same between the inside and other
flame again dividing the line. The small door in the wall
wood side of the flame. At the exit to the left side,
naturally confused reflections of the flame were interspersed on
pewterglass and the interior tunnel. In this manner, eighteen
wooden flue the shape of the opposite window textures the room
other wise natural to the area of the bitse without the first
between the entire small and the interior tunnel was the
door into two sections. One were afraid to the eighteenth room
were placed in back a wall that it divided the inside of the
into front door. The flame with the door in it
a small platform. Its inside were the side inside of
The peep box itself was designed to eliminate possibilities in
window and the light used in reading apparatus of the lion.
Figure it's a close-up of the peep box' mirror the
is a noise in the light glassware air time.
and be heavens wooden. The amount of smoke was indistinct
Ultimate picture-quality (1213^{3}) was placed in the Burton

Figure 11. Close-up View of Test Box.

steadied, readings were taken of the temperature and of the pressure measured by the pitot-static manometer. Then the angle of the tufts was recorded. This was done for three different flows. Photographic records were taken of all runs.

The smoke generator was operated as follows: About 5 cc of $TiCl_4$ were put in the gallon can before the run was started. When smoke was desired, the valve in the high pressure air line was opened. Varying the amount of high pressure air very effectively regulated the amount of smoke obtained. This arrangement gave a very satisfactory supply of smoke under good control. Unfortunately, it was impossible to detect the angle of flow through the holes by this means due to the high velocities and large amount of turbulence.

Results

Table II and Figure 12 show the results of the tests. Photographs taken during the runs are shown in Figures 13, 14, and 15. From the results it can be seen that the flow angle varies from 60° to 35° as the distance downstream increases. There is little variation with change in velocity. The average flow angle over the length of the secondary zone was approximately 45°.

of the measurement error was additionally 4%.

Results is only figure 36 shows the results of the tests. Photographic images obtained from 90% to 70% on the negative test the first media surface from 90% to 70% on the negative figures 37, 38, and 39. Here the results is only figure 36 shows the results of the tests.

Results

media to obtain the right exposition and density numbers of pictures. Therefore, it was calculated the factor of which media light penetrated. This measurement light penetrated the media to obtain the right exposition and density numbers of pictures.

The media densitometer was calibrated as follows: three different films. Photographic exposure meter values of all the media were recorded. Then the transmittance numbers of the photographic negatives. Then the standard, readings were taken of the densitometer and of the

Conclusions

Since the average flow angle is 45°, it is apparent that an effectiveness coefficient is necessary for calculating the flow through the secondary holes. In this analytical design, it seemed reasonable to use the average value of flow angle of 45° over the entire length of the secondary zone. Thus, the effectiveness coefficient is

$$C_e = \sin 45^\circ$$

$$= .707$$

Table II. Flow Angle Through Holes for Various Weight Flows.

Hole No.*	Flow Angle - Degrees Weight Flow - Lb/Sec		
	1.18	1.32	1.45
1	53	62	60
2	46	52	49
3	45	46	46
4	45	45	45
5	42	42	42
6	40	40	40
7	40	37	38
8	38	35	37
9	37	35	35

* Hole number 1 is the first 5/8-inch hole in the test plate. It is located four inches from the entrance to the test box. The successive holes are one inch apart.

Table 1. Plate counts (Petroff-Hausser) for various mitotic stages.

Cell Type*	Time Delta = Interval (Minus Type - Plate)		
	5.1%	1.1%	1.4%
1	51	58	60
2	49	53	47
3	45	44	46
4	41	39	43
5	40	36	42
6	40	34	40
7	39	37	34
8	38	32	37
9	37	29	35

* Cell number 1 is the first G2-type cell in the test plate. It is impossible from the sequence to say what type the succeeding cells are each cell represents

FIGURE 12

FLOW ANGLE THROUGH HOLES FOR PARAVANE WEIGHT FLOW



Figure 13. Interior of Test Box Showing Angle of Silk Tufts During Run at 1.18 Lb/Sec.

Figure 14. Interior of Test Box Showing Angle of Silk Tufts During Run at 1.45 Lb/Sec.

Figure 15. Interior of Test Box During Run in Which Smoke was Used.

Sample Calculations

To find the weight flow through the test box when conditions in the pipe are:

Δh = pitot-static manometer reading = 1/2" H_2O = 2.6 lb/ft^2

Temperature = 130° F or 590° R

$$w = \rho A v$$

where w = weight flow in lb/sec

ρ = density in lb/ft^3

A = area of the eight-inch pipe in ft^2

v = velocity in ft/sec

$$\rho = .0765 \times \frac{520}{590} = .0675 \text{ lb/ft}^3$$

$$A = .785 \times \frac{8^2}{144} = .35 \text{ ft}^2$$

$$v = \sqrt{\frac{2g \times \Delta h}{\rho}}$$

$$= \sqrt{\frac{64.4 \times 2.6}{.0675}}$$

$$= 49.9 \text{ ft/sec}$$

Then, $w = .0675 \times .35 \times 49.9$

$= 1.18$ lb/sec

Answers to Problems

$$= 1.78 \text{ lb/sec}$$

$$\dot{m} = .0520 \times .70 \times 49.8$$

$$= 49.8 \text{ lb/sec}$$

$$\sqrt{\frac{2 g_c \Delta p}{\rho}} = \sqrt{\frac{32.2 \times 2.6}{.0520}}$$

$$A = \sqrt{\frac{\dot{m} \Delta p}{\rho}}$$

$$v = \frac{180}{\frac{p}{\rho}} = \frac{180}{500} = .360 \text{ ft}^3/\text{lb}$$

$$\rho = \frac{1}{v} = \frac{1}{.360} = .0520 \text{ lb/ft}^3$$

R = gas constant in ft/sec^2-°R

T = temperature in °R

p = density in lb/ft^3

μ = viscosity in lb/ft-sec

Δp = pressure drop = 2.6 psi = 374.4 lb/ft^2

Temperature = 1504 R or 1040 R

$$\rho = \frac{p}{RT}$$

$$\rho = \frac{500}{180 \times 1504} = .0520 \text{ lb/ft}^3$$

μ = 1.78 lb/hr-ft

$$\dot{m} = .0520 \times .70 \times 49.8$$

$$= 1.78 \text{ lb/sec}$$

APPENDIX B

SYMBOLS

A - maximum area of combustion chamber

A_1 - clearance area between basket and outer liner

A_2 - entrance area into basket

a - speed of sound

C_e - effectiveness coefficient

C_o - orifice coefficient

$c_{p\,ave}$ - average specific heat at constant pressure

c_{p4} - specific heat at constant pressure at inlet

c_{p5} - specific heat at constant pressure at exit

D - diameter of basket

D_1 - diameter of pipe with area equivalent to A_1

D_h - diameter of each hole in ring

D_{max} - maximum diameter of combustion chamber

D_{id} - inside diameter of clearance area

D_{od} - outside diameter of clearance area

d - minor diameter of tail cone

f - friction factor

g - gravitational constant

h - length of tail cone

I - combustion intensity

L - length from nozzle to turbine entrance

l - length from nozzle to end of basket

l_c - length of cylinder or basket

NOMENCLATURE

l^{ft} = length of airplane or rocket

l = length from nozzle to end of rocket

T = length from nozzle to maximum enlarge

I = acceleration increment

L = length of rear mass

E = displacement constant

i = inertia moment

D^{ft} = nozzle diameter of flange

D^{in} = nozzle diameter of flange

D_{max} = maximum diameter of acceleration chamber

D^{in} = diameter of body in line

D^{ft} = diameter of body at flange

R = diameter of rocket

d^{in} = diameter of nozzle throat

d^{ft} = diameter of nozzle throat

d_{flame} = maximum diameter of flame

D^{in} = nozzle diameter

D^{ft} = diameter of nozzle

c = speed of sound

P^{in} = pressure in rocket

P^{ft} = pressure in rocket

A = section area of accumulator chamber

LHV - lower heating value of fuel

M_r - reference Mach number

M_4 - entrance Mach number

M_5 - exit Mach number

N - number of combustion chambers

N_h - number of holes in ring around basket

NR - Reynolds number

P - pressure

P_{sc} - atmospheric pressure at standard conditions

P_{4s} - entering static pressure

P_{5s} - exit static pressure

ΔP - pressure drop

Q - volume air flow

q - heat input

R - gas constant

T_{sc} - temperature at standard conditions

T_{4s} - entrance static temperature

T_{5s} - exit static temperature

T_{4t} - total inlet temperature

T_{5t} - total exit temperature

V - volume available for combustion

V_C - volume of cylinder or basket

V_H - volume of hemisphere or dome

V_{TC} - volume of tail cone

v - velocity

v_r - reference velocity

a^* = reference velocity

A = velocity

A_{12} = volume of test room

A^0 = volume of thermosphere at sea

A^* = volume of ephinsphere at pressure

A = volume available for communities

T_{0A} = total unit temperature

T_{0T} = total inlet temperature

T_{0E} = unit static temperature

T_{0T} = minimum static temperature

T_{0A} = temperature at standard conditions

H = gas constant

d = heat index

δ = volume air flow

∇P = pressure drop

T_{0A} = cold static pressure

T_{0E} = adjusted static pressure

T_{0A} = stagnation pressure at standard conditions

λ = pressure

μ_0 = Carnotite number

Ω^* = number of holes in ring exhaust nozzle

Σ = number of combustion chambers

Ω^0 = cold flow number

Ω^* = reference temp number

Ω^* = reference temp number

T_{0A} = Tower heating value of heat

v_4 - entrance velocity

v_5 - exit velocity

w - weight flow of air

w_f - weight flow of fuel

γ - ratio of specific heats

η - combustion efficiency

μ - viscosity of air

μ_r - reference viscosity of air

ρ - density of air

ρ_{sc} - density of air at standard conditions

ρ_0 = density of air at standard conditions

ρ = density of air

μ = absolute viscosity of air

ν = kinematic viscosity of air

ζ = coefficient of skin friction

χ = ratio of specific heats

ϕ = angle of slope of plane

ψ = angle of sweep

ω = angular velocity

APPENDIX C

REFERENCES

1. Jet Propulsion, Air Technical Service Command, Restricted, 1946, p. 439.
2. Kay, Stewart, "The Problem of Combustion Chamber Design," paper presented before SAE at National Aeronautical Meeting, April 1946.
3. Development of the British Gas Turbine Jet Unit, Institution of Mechanical Engineers, London, reprinted by ASME, New York, January 1947.
4. Nerad, A. J., General Electric, "Some Aspects of Turbo-Jet Combustion," IAS Reprint #219, March 1949.
5. Ashback, Dvid W., Handbook of Engineering Fundamentals, John Wiley & Sons Inc., New York, 1st edition, 1936, p. 6-35.
6. Binder, R. C., Fluid Mechanics, Prentice-Hall Inc., New York, 1943, p. 100.
7. Ibid, p. 84.
8. Ibid, p. 74.
9. Smith, G. Geoffrey, Gas Turbines and Jet Propulsion for Aircraft, Aircraft Books, Inc., New York, 1945, p. 67.

APPENDIX D

BIBLIOGRAPHY

1. Binder, R. C., Fluid Mechanics, Prentice-Hall Inc., New York, 1943.

2. Bollinger, L. M. and Williams, D. T., "Effect of Reynolds Number in the Turbulent Flow Range on Flame Speeds of Bunsen-Burner Flames," NACA, T. N. 1707, September 1948.

3. Caldwell, F. R., Rueggs, F. W. and Olsen, L. C., "Combustion in Moving Air," SAE Preprint, April 1948.

4. Childs, J. H., McCafferty, R. J. and Marino, C. S., "Effect of Combustor-Inlet Conditions on Performance of an Annular Turbo-jet Combustor," NACA, T. N. 1357, July 1947.

5. Development of the British Gas Turbine Jet Unit, Institution of Mechanical Engineers, London, reprinted by ASME, New York, January 1947.

6. Zabbach, Ovid W., Handbook of Engineering Fundamentals, John Wiley & Sons Inc., New York, 1st edition, 1936.

7. Goldstein, A. W. and others, "Analysis of the Performance of a Jet Engine from Characteristics of the Components," NACA, T. N. 1701, September 1948.

1. Bhatnagar, P. L., Fluid Mechanics, McGraw-Hill Inc., New York, 1960.

2. Hollingdale, S. H. and Gilliams, F. E., "Effect of Impressed Pressure in the Downstream Flow Region on Flame Speeds of Gaseous-Burner Flames," Cmdn, R. M., 1951, Supplement 1960.

3. Lightfoot, E. N., Hanna, W. T. and Olson, D. O., "Apparatus for Heating Air," Gas Processes, April 1960.

4. Stitt, F. N., "Effect of Temperature on Viscosity of Gaseous and Vapour-Liquid Combustion," Cmdn, R. M., 1951, July 1952.

5. Instruments of the British Gas Industry (2nd Edit. 1961. Institution of Gas Engineers, London, Reinhold Pub. Corp., New York, January 1962.

6. Eckert, Ernst R. G., Introduction of Heat Transfer Flow, Flow Fluid & Heat Exch., New York, Int. Edition 1958.

7. Dorfman, L. A., and Krylov, "Analysis of the Laminar Flame of a Jet Engine Flow Characteristics at the Combustion," Cmdn, R. M., 1951, Supplement 1960.

8. Hall, N. A. and Mulready, R. C., "Ideal Temperature Rise from Constant Temperature Combustion of Hydrocarbon Fuels," SAE Preprint, April 1948.

9. Hawthorne, William R., "Factors Affecting the Design of Jet Turbines," SAE Preprint, 1947.

10. Jet Propulsion, Air Technical Command, Restricted, 1946.

11. Johnston, W. C., Westinghouse Electric, "Flame Propagation Rates at Reduced Pressures," SAE Preprint, June 6, 1947.

12. Liepmann, Hans W. and Puckett, Allen E., Introduction to Aerodynamics of a Compressible Fluid, John Wiley & Sons Inc., New York 1947.

13. Lloyd, P., "Determination of Gas-Turbine Combustion Chamber Efficiency by Chemical Means," Trans. ASME, May 1948

14. London, A. L., Stanford University, "Gas-Turbine Plant Combustion Chamber Efficiency," Trans. ASME, May 1948.

15. McLarren, Robert, "Altitude Blow-Out of Jet Engines," Aviation Week, November 24, 1947.

16. Rock, Frank C., "Engineering Development of the Jet Engine and Gas Turbine Burner," SAE Preprint, January 1946.

9. Hall, H. A. and Holmsdale, H. E., "Heat Temperature Time Area Compound Temperature Conversion of Spreadsheet Models," Oak Tree, April 1988.

8. Gretchen, Kathleen F., "Planning Listening the Design of Jet Turbines," Jet Propulsion, 1987.

10. Jet Propulsion, Air Technical Manual, Destroyed, 1988.

11. Johnston, H. O., Investigative Chemistry, "Flame Propagation Rate Under an Imposed Pressure," Jet Propulsion, June 6, 1988.

12. Jayson, Ellen K. and Powell, Alan T., Introduction to Aerodynamics of a Supersonic Flight, John Wiley & Sons, New York 1988.

13. Lipp, T., "Determination of Gas-Turbine Temperature Change Efficiency by Chemical Means," Brown, Lane, May 1988.

14. London, M. L., Jacobs Internationally, "Gas-Turbine Plant Combustion Chamber Efficiency," Trans. ASME, May 1988.

15. Patterson, Robert, "Efficient Development of Jet Engines," Aviation Week, November 28, 1987.

16. Snow, Glenn O., "Engineering Development of Gas Engine Engine and Gas Turbine Blower," Jet Propulsion, January 1988.

17. Nerad, A. J., General Electric, "Some Aspects of Turbo-jet Combustion," IAS Preprint #219, March 1949.

18. Olson, W. T. and Bernardo, E., "Temperature Measurements and Combustion Efficiency in Combustors for Gas-Turbine Engines," Trans. ASME, May 1948.

19. Pinkel, I. I. and Shames, H., "Analysis of Jet-Propulsion Engine Combustion Chamber Pressure Losses," NACA, T. N. 1180, 1947.

20. Smith, G. Geoffrey, Gas Turbines and Jet Propulsion for Aircraft, Aircraft Books Inc., New York, 1946.

21. Way, Stewart, "The Problem of Combustion Chamber Design," paper presented before SAE at National Aeronautical Meeting, April 1946.

DEC 7
29
RENEWED
18
Model
11464
Thesis
V4 Verdin
Analytical design of
a turbo-jet engine
combustion chamber
NOV 1060
10479

thesV4
The analytical design of a turbo-jet com
3 2768 001 92746 0
DUDLEY KNOX LIBRARY